



Power Delivery Charging Station - 72 W

One USB-C Power Delivery Port up to 60 W, Three USB-A Charging Ports Sharing up to 12 W / 2.4 A, Black

Part No.: [102124](#)

EAN-13: 0766623102124 | UPC: 766623102124

Device power with a portable, powerful Power-Delivery charger

Enjoy complete charging power with the Manhattan Power Delivery Charging Station - 72 W. This wall charger's USB-C port uses Power Delivery technology to determine the power needs of your smartphone, tablet or other compatible device and supplies it at the fastest, safest rate it can. The additional USB-A ports supply power at up to 2.4 A to quickly charge your devices. The perfect power companion with its stylish, compact and ultra-modern design, the Manhattan Power Delivery Charging Station - 72 W also intelligently safeguards itself and your devices with its short-circuit-, overvoltage-, overcurrent- and overtemperature-protection functions.

Features:

- Charging station solution with one USB-C Power Delivery (PD 3.0) and three USB-A charging ports
- Charges different devices simultaneously with ideal potential energy
- USB-C PD port delivering up to 60 W to charge a notebook, laptop, Ultrabook™, tablet or other USB-C powered device

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Three USB-A ports sharing 12 W to charge a portable device with each port supporting up to 2.4 A
- Overload, overcurrent and overheating protection
- Compact, portable and stylish design for easy travel
- Three-year warranty

Specifications:

Standards and Certifications

- USB 2.0
- PD 3.0
- FCC
- UL 62368
- CE
- RoHS
- WEEE

Ports

- One USB-C with Power Delivery (PD 3.0)
- Three USB-A

General

- AC input: 100 – 240 V; 50 – 60 Hz
- USB-C output: 5 – 20 V; maximum 3 A; 60 W
- Voltage/current settings (maximum):
 - USB-C:
 - 5 V / 3 A
 - 9 V / 3 A
 - 12 V / 3 A
 - 15 V / 3 A
 - 20 V / 3 A
 - USB-A:
 - up to 5 V / 2.4 A

Input Characteristics

- AC rated voltage: 100 – 240 V
- Frequency range: 50 – 60 Hz (± 1 Hz)
- Current: ≤ 1 A at 100 VAC 60 HZ

Output Characteristics

- Rated voltage: 5 / 9 / 12 / 15 / 20 V
- Current: 3 A maximum (at constant voltage mode)
- Rated power: 72 watts maximum
- Overshoot voltage: $\leq 5\%$

Protection Characteristics

- Short circuit (SCP) with auto-recovery mode

- Overvoltage (OVP) with auto-recovery mode
- Overcurrent (OCP) — current limit: 150% (max)
- Overtemperature (OTP)

Physical

- Dimensions: 9.1 x 7.5 x 2.75 cm (3.58 x 2.95 x 1.08 in)
- Weight: 0.22 kg (7.76 oz.)
- Housing: plastic

Operating Environment

- Operation Temperature: 0 – 30°C (32 – 86°F)
- Storage Temperature: -20 – 65°C (-4 – 149°F)
- Humidity (noncondensing): 10 – 90%

Package Contents

- Power Delivery Charging Station - 72 W
- Power Cord
- Quick Instruction Guide



